## **FEATURES**

- This product finishes continuous carrying, sealing and printing in one operation
- Fitted with an electronic constant temperature control system
- Fitted with a stepless speed adjusting transmission mechanism
- Pure aluminum turbine box, polyoxymethylene gear and a high-power 80W copper core motor ensures high power, stable performance, low noise and high efficiency
- Fitted with an emergency stop switch to stop quickly in case of emergency
- Fitted with a pure copper heating block evenly heated and durable
- The machine is supplied with an embossing wheel and a printing wheel as standard
- The sealing width is 6-12mm, which can be adjusted manually
- Fitted with non-slip feet
- The Vertical continuous sealer allows you to package and seal liquids as well



## VERTICAL SPECIFICATIONS

MODEL
ELECTRICITY
DIMENSIONS
WEIGHT
SEAL WIDTH
OUTPUT
TEMPERATURE RANGE
MAX LOAD

ORDER CODE

SmartVac FR-880-LW 0.85kW, 220V, Single Phase 860 x 420 x 350mm high 20kg

6 ~ 12mm 0 ~ 12m/min

0 ~ 300°C 5kg

SMS0880-LW







## **HORIZONTAL**

## **SPECIFICATIONS**

MODEL
ELECTRICITY
DIMENSIONS
WEIGHT
SEAL WIDTH
OUTPUT
TEMPERATURE RANGE
MAX LOAD

ORDER CODE

SmartVac FR-880 0.85kW, 220V, Single Phase 860 x 420 x 350mm high 19kg

6 ~ 12mm 0 ~ 12m/min

0 ~ 300°C 5kg

SMS0880





