

FEATURES

- 304 Stainless steel body panel
- Electromagnetic drive shaft
- Fitted with an all red copper condenser
- Night-mode setting to save energy
- Includes drip trays

- Durable, high density PC tanks with brandable lids
- Imported European brand compressor, durable, energy saving & low noise
- Dual beater mixing system (inner and outer cooling cylinder) to avoid "ice jam"
- Energy saving LED Lighting on each tank lid for improved aesthetics
- Fitted with non-slip feet







3 x 10 LITRE SLUSH MACHINE

SPECIFICATIONS

0.8kW, 220V, Single Phase 610 x 510 x 770mm high FLECTRICITY DIMENSIONS 63kg WEIGHT (3x) 10Lt -2 to -3°C VOLUME TEMP RANGE REFRIGERANT GAS R404a

ORDER CODE

SMP0310



560mm 660mm

70kg

2 x 10 LITRE SLUSH MACHINE

SPECIFICATIONS

0.6kW, 220V, Single Phase 430 x 510 x 770mm high FLECTRICITY DIMENSIONS WEIGHT 41kg (2x) 10Lt -2 to -3°C VOLUME TEMP RANGE REFRIGERANT GAS R404a

ORDER CODE SMP0210



1 x 10 LITRE SLUSH MACHINE

SPECIFICATIONS

ELECTRICITY 0.6kW, 220V, Single Phase DIMENSIONS 220 x 510 x 770mm high WEIGHT 28kg (1x) 10Lt VOLUME TEMP RANGE REFRIGERANT GAS

R404a

ORDER CODE SMP0110







FEATURES

- Bottom housing manufactured from stainless steel
- Durable PVC tanks
- Easy to use touch control panel.
- Three operation settings Margarita, Slush, and Cold drinks
- LCD display clearly shows the machine operation status
- Independent control system for each tank
- LED lighting for easy nighttime operation and improved aesthetics
- Motor current and compressor overload protection
- Large vents for fast heat dissipation and improved cooling efficiency
 - * Recommended for lite commercial use only. Small and compact design for fewer and smaller servings.



2 x 3 LITRE SLUSH MACHINE

SPECIFICATIONS

ELECTRICITY DIMENSIONS VOLUME WFIGHT TEMP RANGE REFRIGERANT GAS

ORDER CODE

0.4kW, 220V, Single Phase 390 x 490 x 545mm high (2x) 3Lt 27kg -5 to 10°C R290

SMP0203



1 x 3 LITRE SLUSH MACHINE

SPECIFICATIONS

ELECTRICITY DIMENSIONS VOLUME WEIGHT TEMP RANGE REFRIGERANT GAS

240 x 490 x 545mm high (1x) 3Lt 19kg -5 to 10°C R290

0.3kW, 220V, Single Phase

ORDER CODE

SMP0103

