


### **FEATURES**

- Machine body manufactured from stainless steel
- Fitted with an emergency stop button
- Collapsable for space saving purposes
- Overload protection and open-phase protection function Adjustable dough thickness
- Fitted with (4x) casters, 2 lockable







### 630mm BELT

#### **SPECIFICATIONS**

**ELECTRICITY** EXPANDED DIMENSIONS STOWED DIMENSIONS WEIGHT MAX. DOUGH CAPACITY **BELT SIZE** ROLLER ADJUSTABLE GAP

ORDER CODE

1.1kW, 220V, Single Phase 1000 x 3100 x 1100mm high 1000 x 720 x 1700mm high 268kg 6.5kg 630 x 2400mm

PSB-QS-630B

1~ 40mm



# 400mm BELT **SPECIFICATIONS**

**ELECTRICITY** EXPANDED DIMENSIONS STOWED DIMENSIONS WEIGHT MAX. DOUGH CAPACITY **BELT SIZE** ROLLER ADJUSTABLE GAP

ORDER CODE

0.4kW, 220V, Single Phase 760 x 2000 x 1040mm high 760 x 620 x 1310mm high 160kg

4kg 400 x 1600mm 1 ~ 35mm

PSB-QS-400B



# **DOUGH DIVIDER & ROUNDER** SEMI-AUTOMATIC



## **FEATURES**

- Heavy duty rigid cast iron construction
- Self-lubricating, enclosed motor for food safety and low maintenance Stainless steel cutting knives, divides dough into 30 equal pieces
- Includes two divider rounder plates

- Heat treated enamel finish resists rust, scratches and dents
- Dual stage, semi-automatic operation
- Dough pieces can be adjusted between 30 and 100g



#### **SPECIFICATIONS**

**ELECTRICITY** DIMENSIONS WEIGHT OUTPUT DOUGH WEIGHT PROCESSING TIME

0.75kW, 220V, Single Phase 550 x 720 x 1350mm high 290kg 30pcs 30 ~ 100g per piece (3kg Max) 10 ~ 13 seconds

